
HDTV - IRD GUIDELINES AUSTRIA

Version 3.4 –04 September 2014

Notice

This document is property of Österreichische Rundfunksender GmbH & Co. KG, hereafter ORS, and may not be reproduced, modified and/or diffused in any way without the explicit prior written permission of ORS.

By using this specification in any form, the reader unconditionally acknowledges and accepts that ORS shall have no liability or responsibility whatsoever to customer or any other person or entity with respect to any loss or damage caused or alleged to be caused directly or indirectly by services provided by us.

The information contained in this document is subject to change without notification.

TABLE OF CONTENTS

1	INTRODUCTION	5
1.1	Scope	5
1.2	Document History	5
1.3	Terminology	6
1.4	Definitions	6
1.5	References	9
2	GENERAL REQUIREMENTS	11
3	HARDWARE REQUIREMENTS	11
3.1	Satellite tuner and demodulator	11
3.1.1	General	11
3.1.2	RF/IF characteristics	11
3.1.3	Demodulation and error correction	11
3.1.4	Input frequency range/tuning range	12
3.1.5	Tuning/scanning procedures	12
3.1.6	Satellite tuner interface and signal levels	15
3.2	MPEG-2 demultiplexer	15
3.2.1	General	15
3.2.2	DVB descrambler	16
3.3	Video decoding	16
3.3.1	SDTV	16
3.3.2	HDTV	17
3.4	Audio decoding	18
3.4.1	Multichannel audio	18
3.5	HDTV IRD interfaces	19
3.5.1	SCART interface	19
3.5.2	Digital audio/video interface (HDMI)	19
3.5.3	Component video (YPbPr)	20
3.5.4	Audio interfaces	20
3.5.5	Data interface	20
3.5.6	DVB common interface	21
4	SERVICE INFORMATION	22
5	NAVIGATOR AND EPG	22

6	TELETEXT AND DVB SUBTITLING	23
6.1	Teletext	23
6.1.1	Display of Teletext	23
6.1.2	Teletext data in the VBI	23
6.2	DVB subtitling	23
7	CONDITIONAL ACCESS AND DIGITAL RIGHTS MANAGEMENT	24
7.1	Conditional access system	24
7.2	Secure Chipset Pairing	25
7.3	Maturity rating	25
7.4	Content security	25
7.4.1	Digital Copy Protection	25
7.4.2	Analogue Copy Protection	26
7.4.3	Component video control	26
7.4.4	Storage rights	26
7.4.5	Storage Rights for IRDs with non-embedded CA System	27
7.5	General rules on content immutability	28
7.5.1	No modification to programme signals	28
7.5.2	No graphical overlays	28
7.5.3	No concurrent display of programme signals and other content	28
7.5.4	No rescaling of the programme signal	29
7.5.5	No automatic Ad Zapping	29
8	DIGITAL VIDEO RECORDER (DVR)	29
8.1	Content security	29
8.2	DVR scheduling	29
8.3	Maturity rating	29
9	HYBRID BROADCAST TELEVISION	30
10	SYSTEM SOFTWARE UPDATE	30
10.1	SSU over-the-air (broadcast download)	30
10.2	Local download	31

1 INTRODUCTION

1.1 Scope

This document outlines a set of minimum requirements for HDTV IRDs (integrated receiver decoders), conditional access modules and TV sets with an integrated HDTV IRD used for receiving SD (Standard Definition) and HD (High Definition) satellite television programs distributed by ORS for the Austrian market.

Exceptions for HDTV IRDs, which are integrated into TV sets, are set out explicitly within the affected clause.

Requirements which apply only to HDTV IRDs with PVR or PVR-ready functionality are explicitly outlined.

This guideline defines only a minimum set of requirements and is not intended to be a complete specification for HDTV IRDs. It lists the minimum requirements for receiving digital audio and/or video in either standard or high definition, and/or data services distributed via satellite.

1.2 Document History

Version	Date	Comments
0.1	12.11.2007	Initial version.
0.2	19.11.2007	Draft version.
0.3	22.11.2007	Modifications after 1 st review.
0.4	26.11.2007	Modifications after 2 nd review.
0.5	07.12.2007	HDCP Specification
1.0	08.01.2008	Changes regarding content protection. Release version.
2.0	02.06.2009	Changes regarding the Irdeto CA system, merging with the SDTV IRD guideline and additional requirements for the smart card agreement
2.1	16.02.2010	Cryptoworks no longer supported. Requirement for channel list management added. General requirements adapted. PVR feature added. AC3 handling defined. Composite interface added.
2.3	09.03.2010	Requirements for TV sets with integrated IRD
2.4	24.03.2010	Additional requirements for CI
2.5	21.05.2010	LCN added
2.6	21.05.2010	DRM & content protection added Middleware
2.7	31.05.2010	HDTV basic requirements Maturity rating Operator pairing

		DRM & Content protection via Irdeto ECM
2.8	01.06.2010	HDTV mandatory, SDTV-only no more specified
2.9	07.07.2010	DRM, CP, general rules adapted
3.0	23.08.2010	Analogue interfaces not mandatory, final clean version 3
3.1	01.09.2012	Irdeto no longer required for storage encryption Proof-reading
3.4	07.01.2014	Changed requirements for channel lists. HbbTV mandatory for internet connected IRDs.

1.3 Terminology

Shall (mandatory)	Denotes that the item is mandatory.
Should (recommended)	Denotes that the item is not mandatory, but highly recommended.
May (allowed)	Denotes that the item is allowed.

1.4 Definitions

AAC-HE	Advanced Audio Coding High Efficiency
AC-3	Audio Coding 3 (also known as Dolby Digital)
AD	Audio Description (scene description for visually impaired)
AIT	Application Information Table
API	Application Programming Interface
AVC	Advanced Video Coding
BAT	Bouquet Association Table
CA	Conditional Access
CAM	Conditional Access Module
CAT	Conditional Access Table
CI	Common Interface
CI+	Common Interface Plus
CRC	Cyclic Redundancy Check
CSA	Common Scrambling Algorithm
CVBS	Color, Video, Blank And Sync
DRM	Digital Rights Management
DTS	Digital Theatre Sound
DTT	Digital Terrestrial Television
DVB	Digital Video Broadcasting
DVB SSU	DVB System Software Update.
DVB-T	Digital Video Broadcasting - Terrestrial
DVB-T2	Digital Video Broadcasting – Second Generation Terrestrial
DVR	Digital Video Recorder. An IRD, which is capable of recording content of a DVB Transportstream on the IRD internal data storage or external data storage.

E-AC-3	Enhanced AC-3 (also known as Dolby Digital Plus)
EICTA	European Information & Communications Technology Industry Association
EIT	Event Information Table
EITp/f	Event Information Table, present/following
EITsch	Event Information Table, schedule
EPG	Electronic Program Guide
ETSI	European Telecommunications Standards Institute
H.264	H.264 is a standard for video compression. It is also known as MPEG-4 Part 10, or MPEG-4 AVC (for Advanced Video Coding).
HbbTV	Hybrid broadcast broadband Tele Vision.
HE AAC	MPEG-4 High Efficiency Advanced Audio Coding
HE-AAC V2	MPEG-4 High Efficiency Advanced Audio Coding version 2 (also known as aacPlusv2 and eAAC+)
HD	High Definition
HDCP	High-bandwidth Digital Content Protection
HDTV	High Definition Television
HDMI	High Definition Multi-media Interface
iDTV	Integrated Digital TV set
IRD	Integrated Receiver Decoder:
IRD vendor	The IRD vendor is understood as a distributor who is amended to offer and sell certified IRDs in the Austrian market, according to the defined trade arrangement.
LCN	Logical Channel Number
Mb	Megabit
MFN	Multi-Frequency Network
MPEG	Motion Picture Experts Group
NID	Network ID
NIT	Network Information Table
ONID	Original Network ID
ORF	Österreichischer Rundfunk
ORS	Österreichische Rundfunksender
ORS comm	ORS comm GmbH & Co KG
OSD	On Screen Display
OTA	Over the air
PAT	Programme Association Table
PID	Program Identifier
PIN	Personal Identification Number
PiP	Simultaneous display of the unchanged video content of two independent live video sources on one screen.
PMT	Program Map Table
PVR	Personal Video Recorder, see also DVR
PSI	Program Specific Information
RCA	Radio Corporation of America
RF	Radio Frequency

SCART	Syndicat des Constructeurs d'Appareils Radiorécepteurs et Téléviseurs / Radio and Television Receiver Manufacturers'
SD	Standard Definition
SDT	Service Description Table
SDTV	Standard Definition Television
SFN	Single Frequency Network
SGT	Service Guide Table
SI	Service Information
SID	Service ID
SSU	System Software Update...
TS	Transport Stream
TV Set	The term "TV Set" describes within this document the integrated combination of an IRD and a display. See also iDTV.
UI	User Interface
USB	Universal Serial Bus

1.5 References

[1]	DVB A 011	DVB A 011 Common Scrambling Algorithm. DVB Blue Book A011.
[2]	ETSI EN 300 421 v1.1.2	Digital Video Broadcasting (DVB); Digital broadcasting systems for television, sound and data services: Framing structure, channel coding and modulation for 11/12 GHz Satellite services.
[3]	ETSI EN 302 307 v1.2.1	Digital Video Broadcasting (DVB); Second generation framing structure, channel coding and modulation systems for Broadcasting, Interactive Services, News Gathering and other broadband satellite applications.
[4]	IEC 60169-2	Radio-frequency connectors, Part 2: Coaxial unmatched connector
[5]	ETSI TS 101 154 v1.9.1	Digital Video Broadcasting (DVB); Implementation guidelines for the use of Video and Audio Coding in Broadcasting Applications based on the MPEG-2 Transport Stream
[6]	ISO/IEC 13818-1	Information technology - Generic coding of moving pictures and associated audio information. Part 1: Systems.
[7]	ISO 639-2	Code for the representation of names of languages
[8]	ITU-T V.92	Enhancements to Recommendation V.90
[9]	ETSI EN 50049-1	Domestic and similar electronic equipment interconnection requirements: Peritelevision connector
[10]	ETSI EN 50157-2-1	Domestic and similar equipment interconnection requirements: AV.link-Part 2-1: Signal quality matching and automatic selection of source devices
[11]	ETSI EN 300 468 v1.11.1	Digital Video Broadcasting; Specification for Service Information (SI) in DVB Systems
[12]	ETSI TR 101 211 v1.9.1	Digital Video Broadcasting (DVB); Guidelines on implementation and usage of Service Information (SI)
[13]	ETSI TS 102 006	Digital Video Broadcasting (DVB); Specification for System Software Update in DVB Systems
[14]	ETSI EN 300 472 v1.3.1	Digital Video Broadcasting (DVB); Specification for conveying ITU-R System B Teletext in DVB bitstreams
[15]	ETSI ETR 289	Digital Video Broadcasting (DVB); Support for use of scrambling and Conditional Access (CA) within digital broadcasting systems.
[16]	ETSI TS 102 201 v1.2.1	Digital Video Broadcasting (DVB); Interfaces for DVB Integrated Receiver and Decoder (DVB-IRD)
[17]	Universal Serial Bus	Universal Serial Bus (USB) Specification, Revision 2.0, April 27, 2000.
[18]	ITU-R BT.653-3	Teletext systems
[19]	ETSI EN 300 743 v1.3.1	Digital Video Broadcasting (DVB); Subtitling systems
[20]	ETSI EN 50221	Common Interface Specification for Conditional Access and other Digital Video Broadcasting Decoder Applications
[21]	ETSI TS 102 825	Digital Video Broadcasting Content Protection & Copy Management (DVB-CPCM)

[22]	EBU Tech 3333	EBU HDTV Receiver Requirements, March 2009
[23]	CI Plus Specification	CI Plus Specification v1.2 or recent version
[24]	Logical Channel Numbering (LCN) scheme for large DVB-S platforms, v2.1	ASTRA, Logical channel numbering (LCN) scheme for large DVB-S platforms, technical specification v2.1; 22 June 2009
[25]	ETSI TS 102 796 v1.1.1	ETSI TS 102 796 V1.1.1. Hybrid Broadcast Broadband TV (HbbTV)
[26]	Softcell DVB client	Irdeto, Softcell DVB client, integration guide, Version 3.15 or recent version
[27]	HDMI Specification v1.3	HDMI Licensing LLC, High-Definition Multimedia Interface Specification Version 1.3
[28]	ETSI TS 102 796 V1.2.1.	ETSI TS 102 796 V1.2.1. Hybrid Broadcast Broadband TV (HbbTV) Extension for "Version 1.5", http://www.hbbtv.org/pages/about_hbbtv/HbbTV-specification-1-5.pdf
[29]	Ethernet	Fast Ethernet IEEE 802.3u
[30]	IEEE 802.11.a/b/g/n Wi-Fi	IEEE Wireless Communications Protocols
[31]	Irdeto Complementary IRD specifications for the Austrian market	Irdeto Complementary IRD specifications for the Austrian market version 1.1 or recent version

2 GENERAL REQUIREMENTS

Compliance with general EBU requirements for HDTV receivers as described in EBU Tech 3333 [22] is recommended.

Compliance with the general requirements of applicable European Community directives is mandatory (CE marking).

The user shall be able to store preferences in the persistent memory of the HDTV IRD.

If the HDTV IRD is switched on from standby mode, the HDTV IRD shall tune to the last viewed service.

3 HARDWARE REQUIREMENTS

3.1 Satellite tuner and demodulator

3.1.1 General

The HDTV IRD shall include one tuner/demodulator unit to receive signals from a satellite RF outdoor unit.

The HDTV IRD should have an RF bypass (RF in - RF out). *(Not required for TV sets)*

3.1.2 RF/IF characteristics

The available transponder bandwidths and transponder powers vary with the different satellites. Consequently, a range of symbol rates and forward error correction rates may be employed.

The HDTV IRD shall accept incoming digital DVB signals which comply with DVB-S, as specified in ETSI EN 300 421 [2], and which comply with DVB-S2, as specified in ETSI EN 302 307 [3] (application area: broadcast services).

The HDTV IRD shall accept symbol rates on the incoming carrier up to 45Mbd in case of DVB-S signals and 10Mbd to 30Mbd in case of DVB-S2 signals.

3.1.3 Demodulation and error correction

Demodulation and error correction shall be performed for all symbol rates given above and for all error correction rates specified in ETSI EN 300 421 [2] and ETSI EN 302 307 [3] (application area: broadcast services).

The HDTV IRD shall support QPSK and 8PSK Demodulation as specified in ETSI EN 300 421 [2] and ETSI EN 302 307 [3] (application area: broadcast services).

The HDTV IRD shall support DVB-S compliant FEC (Viterbi) and advanced modulation LDPC/BCH FEC as specified in ETSI EN 300 421 [2] and ETSI EN 302 307 [3] (application area: broadcast services).

3.1.4 Input frequency range/tuning range

The input frequency band of the RF unit with antenna may cover the frequency range 10.7GHz to 12.75GHz for each of two polarisations. The RF unit may be configured to select and convert any of the four 1 GHz bands (upper or lower half band for each polarization) to IF.

The IRD shall be able to tune to any DVB carrier located within the IF band 950-2150 MHz with characteristics and symbol rate as specified in section 3.1.2.

3.1.5 Tuning/scanning procedures

3.1.5.1 General

The HDTV IRD shall provide basic information regarding signal strength and reception quality in a submenu of the HDTV IRD configuration menu.

The HDTV IRD shall provide a scanning procedure over the whole frequency range.

The HDTV IRD should use the scanning procedure to access the services available on the network.

3.1.5.2 Channel lists

The HDTV IRD shall have a preinstalled channel list observing the requirements of lit. a) and b) in this chapter (“Mandatory Channel list”). However, the HDTV IRD may provide further preinstalled channel lists which do not have to observe the requirements of lit. b) (“Optional Channel list(s)”). For the sake of clarity, the requirements of lit. a), lit. c) and d) have to be observed by all channel lists.

In case the HDTV IRD provides more than one channel list, the Mandatory Channel list shall be offered as the first choice in the overall offer of channel lists. This requirement especially applies to the first time installation process.

a. ORF channels

The HDTV IRD shall have a channel list which places the ORF services as follows:

The service ORF 1 HD shall be listed on channel number 1.

One of the nine regional ORF2 <region> HD services shall be listed on channel number 2 as follows:

During the first time installation process of the HDTV IRD, the user should be able to select one of the nine ORF 2 HD regional services

ORF2 B HD	<ORF regional service for Burgenland>
ORF2 K HD	<ORF regional service for Kärnten>
ORF2 N HD	<ORF regional service for Niederösterreich>
ORF2 O HD	<ORF regional service for Oberösterreich>
ORF2 S HD	<ORF regional service for Salzburg>
ORF2 St HD	<ORF regional service for Steiermark>
ORF2 T HD	<ORF regional service for Tirol>
ORF2 V HD	<ORF regional service for Vorarlberg>
ORF2 W HD	<ORF regional service for Wien>

The remaining eight or all nine regional ORF 2 HD services as well as Hitradio OE3 and ORF2E service shall be listed under channel number 100 or at the end of the channel list, in subsequent order.

In case the HDTV IRD does not support the selection of the regional ORF 2 HD service as described above, the service ORF 2 W HD shall be listed on channel number 2.

The service ORF III HD shall not be listed above channel number 15.

The service ORF Sport + HD shall not be listed above channel number 20.

b. Other channels

The channel numbers 1 to 99 must not list any service that requires an activation from a third party in addition to the basic general activation by ORF-digital.

c. Manual changes to the channel list:

Within the channel list view, users shall be able to manually change the order of channels and insert, replace or delete channels at their discretion and therefore manually change the mapping of channel numbers to channel names. In such cases however, the HDTV IRD shall provide an option in the

HDTV IRD setup menu to reset the mappings to the mandatory or optional channel list.

d. Automatic update of the channel list:

The HDTV IRD may provide for an automatic update of the channel list. All requirements of this clause also apply to any automatic update of the channel list.

In case of an automatic update, the user shall receive an on-screen dialog allowing him to accept or refuse such an update of the channel list.

The HDTV IRD shall remember the manual changes made to the channel list view by the user and react accordingly to the current signal.

3.1.5.3 Dynamic NIT and SDT processing

The HDTV IRD should update the modulation parameters according the NIT. Dynamic changes of service names in SDT shall be supported.

3.1.5.4 Dynamic PMT processing

The HDTV IRD shall be able to handle dynamic changes in the program map table (PMT).

An example of a practical use scenario for dynamic PMT changes is a broadcaster's requirement to make it possible to switch on and off regional variants of programs.

The HDTV IRD shall handle dynamic PMT changes in the correct manner and certain additional restrictions shall also be observed:

- Dynamic changes in the PMT shall not produce any disturbances in the audio/video output.
- In cases where switching of elementary audio and/or video streams is triggered, the maximum switching time (measured from PMT update to clear picture) shall be 3 seconds. The maximum switching time shall be met regardless of whether or not the elementary streams are scrambled.

It is recommended, that the video stream should freeze until the new video stream can be displayed.

The HDTV-IRD shall be able to handle a dynamic switchover from an H.264/AVC HDTV elementary stream to an H.264/AVC SDTV elementary stream. The maximum outage shall be less than 3 seconds.

3.1.6 Satellite tuner interface and signal levels

3.1.6.1 RF input connector

The HDTV IRD shall include one input connector, type: IEC 60169-2 [4], F-type, female, 75 ohms.

3.1.6.2 RF output connector

The HDTV IRD should include one output connector, type: IEC 60169-2 [4], F-type, female, 75 ohms.

The RF output shall be available independently from the operational status of the HDTV IRD (operational or stand by), so that there is no restriction on the operation of the connected equipment.

3.1.6.3 Signal level

The HDTV IRD shall accept input signals with a level within the range -25dBm to -60dBm.

3.1.6.4 Power supply and control signals of the RF unit

The HDTV IRD shall provide a power supply and control signals to the external RF unit as specified below:

- Voltage: 13.5/18.5 V +/- 5%
- Current: at least 400 mA
- Control tone:
 - amplitude: 0.65 V +/- 0.25 V
 - frequency: 22 kHz, duty cycle: 50% +/- 10%

The tuner/demodulator shall be able to select between at least two RF units, upper and lower band as well as polarisation within each unit.

The HDTV IRD should support the DiSEqC 1.0 specification.

3.2 MPEG-2 demultiplexer

3.2.1 General

The HDTV IRD demultiplexer shall be compliant with the MPEG-2 transport layer defined in ISO/IEC 13818-1 [6].

The HDTV IRD shall support ETSI TS 101 154 v1.7.1 [5].

Additional requirements:

The HDTV IRD shall interpret the Conditional Access (CA) descriptor as defined in ETSI ETR 289 [15].

The HDTV IRD shall be able to decode an ISO/IEC13818-1 [6] stream with data rates up to 58 Mbps.

The HDTV IRD shall be capable of utilising at least 32 elementary streams simultaneously, which requires 32 PID filters.

The HDTV IRD shall provide at least 32 section filters.

The HDTV IRD shall support variable bit rate elementary streams within a constant bit rate transport stream.

3.2.2 DVB descrambler

The descrambler unit shall be based on the common scrambling algorithm (CSA) as specified by DVB, see DVB A 011 [1].

The HDTV IRD shall be able to evaluate the CA descriptor regardless of whether it is inserted in the PMT at programme level or at programme element level.

3.3 Video decoding

The HDTV IRD video decoding subsystem shall comply with ETSI TS 101 154 v1.7.1 [5] and shall comply with ETSI EN 302 307 V1.1.2 [3]. Still pictures shall be supported in all modes listed below.

3.3.1 SDTV

3.3.1.1 MPEG-2

The HDTV IRD shall comply with ETSI TS 101 154 v1.7.1 [5], sub-clause 5.1, "25 Hz MPEG-2 SDTV IRDs and Bitstreams".

The minimum requirements are:

- The HDTV IRD shall support MPEG-2 main profile main level bitstreams (MPEG-2 MP@ML).
- The HDTV IRD shall support the decoding and display of video material with a frame rate of 25 Hz interlaced.
- The HDTV IRD shall be able to decode bit-streams with 4:3 and 16:9 aspect ratios.
- The HDTV IRD shall support a luminance resolution of 352x576 to 720x576.
- A minimum bandwidth of 300kbps shall be supported.

3.3.1.2 H.264/AVC

The HDTV IRD shall comply with ETSI TS 101 154 v1.7.1 [5], sub-clause 5.6.2, “25 Hz H.264/AVC SDTV IRD and Bitstream”.

The minimum requirements are:

- The HDTV IRD shall support decoding and displaying of H.264/AVC main profile level 3 bitstreams.
- The HDTV IRD shall support the decoding and display of video material with a frame rate of 25 Hz interlaced or progressive.
- The HDTV IRD shall be able to decode bitstreams with 4:3 and 16:9 aspect ratios.
- The HDTV IRD shall support a luminance resolution of 352x576 to 720x576.
- A minimum bandwidth of 300kbps shall be supported.

3.3.1.3 16:9 Letterbox conversion

It shall be possible for the user to switch the aspect ratio between 4:3 and 16:9 (adjustable in the user preferences submenu). *(Not required for TV sets).*

In cases where a 4:3 aspect ratio is preset in the HDTV IRD user preferences settings and video with an aspect ratio of 16:9 is to be displayed, the HDTV IRD shall automatically perform a 16:9 letterbox conversion. *(Not required for TV sets).*

TV sets shall display the video in the correct aspect ratio by adding pillar box or letterbox spacing.

3.3.2 HDTV

3.3.2.1 H.264/AVC

The HDTV IRD shall comply with ETSI TS 101 154 v1.7.1 [5], sub-clause 5.7.2, “25 Hz H.264/AVC HDTV IRD and Bitstream”.

The minimum requirements are:

- The HDTV IRD shall support decoding and displaying of H.264/AVC high profile level 4 bitstreams.
- The HDTV IRD shall support the decoding and display of video material with a frame rate of 25 Hz interlaced or progressive, or 50 Hz progressive.
- The HDTV IRD shall be able to decode bitstreams with 16:9 aspect ratio.

- The HDTV IRD shall support a maximum luminance resolution of 1920x1080.
- A minimum bandwidth of 1 Mbps shall be supported.

The following HD video formats shall be supported:

- 1280x720p/50
- 1920x1080i/25

3.3.2.2 Downscaling from HDTV to SDTV

If the HDTV IRD is equipped with analogue video interfaces, the downscaled HDTV signal displayed on the analogue output shall be at least the same quality and resolution as the full resolution for a PAL SDTV signal. The aspect ratio conversion shall be handled as described in clause 3.3.1.2.

The analogue output shall be controlled by the content security system as described in clause 7.4.

3.4 Audio decoding

The HDTV IRD audio decoding subsystem shall comply with ETSI TS 101 154 v1.7.1 [5], in particular with sub-clause 6 (“Audio”) and its related annexes.

The HDTV IRD shall keep in sync the audio/video streams that are produced in order to achieve adequate lip-synchronization.

The audio decoder shall support the following audio coding systems:

- MPEG-1 Audio Layer I and II
- Dolby Digital (AC-3)

3.4.1 Multichannel audio

3.4.1.1 Digital audio Interface

The HDTV IRD shall be able to output the audio stream in the native incoming audio format of the selected audio component on the digital audio interfaces (see clause 3.5.4.2) in accordance with the requirements of clauses 3.5.2 and 7.4.

In the case of an AC-3 multi-channel audio stream, the audio format shall be optionally available as a stereo downmix on the digital audio interfaces

This clause is also valid for TV sets, in cases where a digital multichannel audio interface is available.

3.4.1.2 Analogue audio interface

If present, the AC-3 multi-channel audio stream shall be decoded to a stereo downmix and shall be fed to the analogue stereo output connectors (see clause 3.5.4.1).

This clause is also valid for TV sets, in cases where analogue audio interfaces are available.

3.4.1.3 Dynamic audio component switching

In cases where the selected AC3 component is turned off inside the selected service during playback, the audio decoder shall automatically select one of the remaining audio components for digital and analogue output. During the switching period, the interruption should be shorter than 3 seconds.

3.5 HDTV IRD interfaces

3.5.1 SCART interface

The HDTV IRD should have one SCART interface or a Composite interface. *(Does not apply to TV sets).*

The SCART interface shall comply with ETSI EN 50049-1 [9] and ETSI EN 50157-2 [10].

This clause is also valid for TV sets, in cases where a SCART interface for video output is available.

3.5.2 Digital audio/video interface (HDMI)

The HDTV IRD shall have at least one HDMI output as described in ETSI TS 102 201 [16], sub-clause 4.6. All digital Video Interfaces shall be compliant to the HDMI specification version 1.3 [27] or higher.

The HDTV IRD shall provide digital copy-protection at HDMI output as defined in the HDMI specification. The HDTV IRD shall provide for the user an option in the system menu to disable the HDCP authentication for unprotected content (see EBU Tech 3333 [22], §9.5). The HDMI source (HDTV IRD) shall attempt authentication if the content requires protection. A

successful HDCP authentication shall always trigger encrypted transmission of the content.

If the content is signalled as digital copy-protected content and the HDCP authentication handshake is successful, then the HDCP command ENC_EN triggering the encrypted transmission of content shall be sent by the HDCP transmitter. If the content is signalled as digital copy-protected content and the HDCP authentication handshake fails at any time during the transmission, then unencrypted (clear) content shall not be transmitted.

Clause 3.5.2 is also valid for TV sets, in cases where an HDMI interface for video output is available.

3.5.3 Component video (YPbPr)

The HDTV IRD should have analogue component video output (YPbPr, RCA connectors). The analogue component video output shall support high-definition resolution.

The clause 3.5.3 is also valid for TV Sets, in cases where a component interface for video output is available.

3.5.4 Audio interfaces

3.5.4.1 Analogue audio

The HDTV IRD should have an analogue audio stereo output (left and right channel RCA connectors).

3.5.4.2 Digital audio

The HDTV IRD shall have a digital audio S/PDIF output (electrical or optical connector).

Digital audio shall be available on all HDMI interfaces and S/PDIF outputs.

Clause 3.5.4 is also valid for TV sets, in cases where a component interface for video output is available.

3.5.5 Data interface

The HDTV IRD should support at least one of the following local data interfaces.

- RS232C as defined in ETSI TS 102 201 [16], sub-clause 4.7.1

- Universal serial bus port, USB 2.0 [17]
- LAN: fast Ethernet IEEE 802.3u and/or WLAN 802.11g (or higher)

In cases where the HDTV IRD contains middleware as described in clause 9, a wired or wireless LAN connection shall be supported.

3.5.6 DVB common interface

In cases where the HDTV IRD lacks an embedded Irdeto CA system as required by clause 7.1, the HDTV IRD shall be equipped with at least one DVB common interface slot in compliance with the common interface specification ETSI EN 50221 [20].

In addition to ETSI EN 50221 [20], audio and video streams shall be scrambled at any point in the physical interface between the connected CA module and the HDTV IRD if the incoming stream is also scrambled.

The CA Module shall be capable of signaling and activating any content protection and DRM functionality to the HDTV IRD as required in clauses 7.2 and 7.4 in a secure way that is not open to being circumvented.

The applied technology for realising this secure content exchange via CI may be based on the common interface plus specification v1.2 [23].

4 SERVICE INFORMATION

The HDTV IRD shall be able to process incoming MPEG-2 TS PSI and DVB SI data (descriptors, tables) in accordance with ETSI EN 300 468 v1.7.1 [11] and ETSI TR 101 211 v1.7.1 [12].

The HDTV IRD shall be able to process the DVB-SI tables for 'actual' and 'other' transport streams.

The following tables are a mandatory set of tables that the HDTV IRD shall be able to process: PAT, PMT, CAT, NIT, SDT, EIT, TDT, TOT

The HDTV IRD shall process the following EIT tables:

- EIT actual (present/following/scheduled)
- EIT other (present/following/scheduled)

The following descriptors in the EIT shall be processed by the HDTV IRD: content_descriptor, short_event_descriptor, extended_event_descriptor.

The HDTV IRD shall process the copy control descriptor as described in clause 7.4.

Descriptors or other data structures that are currently undefined or are unknown to the HDTV IRD shall be skipped and shall not cause any harm.

The HDTV IRD shall support an extended_event_descriptor of up to 1,000 characters per event. A minimum of 200 events per service shall be handled and shall be displayed in the EPG schedule.

5 NAVIGATOR AND EPG

The HDTV IRD shall implement a Navigator, allowing the user to control the operation of the HDTV IRD, and providing user access to system information (user preferences settings, system settings, facilities to initiate system software updates etc).

The Navigator is by definition part of the system software.

The Navigator shall support the German language in all menus and submenus.

The Navigator shall include a basic electronic programme guide which displays information extracted from relevant DVB-SI tables as described in clause 4.

The HDTV IRD shall be able to read and use ISO 639-2 [7] language descriptors associated with the audio streams in the MPEG-2 transport stream ISO/IEC 13818-1 [6].

The user shall be able to set storable preferences for the default audio language. If an audio stream for the default audio language is available for the service the HDTV IRD shall automatically choose that audio stream. In addition, the user shall be able to manually select from all audio streams available within the active service.

6 TELETEXT AND DVB SUBTITLING

6.1 Teletext

During normal operation (decoding of video/audio/data-streams), the HDTV IRD shall be able to demultiplex in parallel the Teletext service transmitted in a packetised format in accordance with ETSI EN 300 472 [14].

The Teletext function shall be easily available via remote control interaction.

6.1.1 Display of Teletext

The HDTV IRD shall be able to insert Teletext via On Screen Display functionality on all available digital and analogue outputs .

TV sets shall display Teletext via On Screen Display functionality. The insertion of Teletext via On Screen Display functionality on available digital and analogue outputs is only recommended for TV sets.

Teletext subtitles shall be displayed synchronous with video. The correct and dynamic display of Teletext subtitles is mandatory.

6.1.2 Teletext data in the VBI

The insertion of the Teletext data in the VBI of the analogue CVBS video output is recommended.

VBI insertion shall conform to ITU-R BT.653-3 [18].

Clause 6.1.2 is also valid for TV sets, in cases where an analogue interface for video output is available.

(Not required for TV sets)

6.2 DVB subtitling

The HDTV IRD should be capable of decoding and displaying DVB subtitle services which are transmitted in conformance with ETSI EN 300 743 [19].

The user shall be able to enable and disable subtitles through the user interface.

If both DVB-subtitling and Teletext subtitling are received simultaneously, the HDTV IRD shall only display the DVB-subtitling stream.

7 CONDITIONAL ACCESS AND DIGITAL RIGHTS MANAGEMENT

7.1 Conditional access system

The HDTV IRD shall support conditional access (CA) in one of the following ways:

Embedded CA system

or

Embedded CA system and one or more common interface slot(s) for CAMs

or

One or more common interface slot(s) for CAMs

Each CI slot in the HDTV IRD shall be in compliance with the DVB common interface specification ETSI EN 50221 [20] and the additional requirements as described in clause 3.5.6.

The CA system in use for ORF's TV services is Irdeto with the CA system ID "0x0648" with the Operator Variant ID "237".

The CA system ID should not be hardcoded into the firmware, but read from the smartcard instead.

The Operator Variant ID shall be hardcoded into the firmware.

The Irdeto embedded CA system has to be integrated according to Irdeto rules (see [26]) and the test procedure and licensing terms as defined by Irdeto have to be observed. This also applies to and is mandatory for any subsequent updates to the Irdeto CA system. The HDTV IRD vendor has to provide to ORS a written and certified proof that the HDTV IRD fulfils all requirements as stipulated in the specification for the Austrian market provided by the CA system vendor Irdeto [31].

7.2 Secure Chipset Pairing

The CA system shall support Secure Chipset Pairing functionality based on IrdeTo's specification.

This also applies to conditional access modules.

7.3 Maturity rating

The HDTV IRD shall support maturity rating as provided by the CA system provider listed in clause 7.1.

7.4 Content security

The HDTV IRD shall support all content security features listed in this clause and its sub clauses either via an embedded CA system or via a CA system residing in a CA-Module.

All signalling of copy-protection and DRM information shall be done within the ECMs of the CA system provider defined in clause 7.1.

In the case of encrypted content, the HDTV IRD shall apply the copy-protection and DRM measures to the related service components as signalled in the ECMs accordingly.

In addition to the ECM-contained metadata, DRM and copy-protection information are also available entirely or partly in the copy control descriptor of the EIT according to [11]. The IRD should decode and display this information inside the shown present/following programme information and the EPG schedule.

In case of unencrypted content the HDTV IRD should support the requirements listed in EBU TECH 3333 [22], §9.7.

7.4.1 Digital Copy Protection

The activation of digital copy-protection is signalled in ECMs defined by the CA system provider listed in clause 7.1.

If digital copy-protection is signalled as active, then copy-protection shall be enabled on all relevant digital interfaces. Please refer also to clause 3.5.2.

In addition to the signalling of digital copy-protection within ECMs, digital copy-protection is signalled in the EIT/copy control descriptor as active by setting the digital copy-protection bit to 1.

7.4.2 Analogue Copy Protection

The activation of analogue copy-protection is signalled in ECMs defined by the CA system provider listed in clause 7.1.

If analogue copy-protection is signalled as active, then either all relevant analogue interfaces (see clause 3.5.1) shall be disabled, or appropriate actions to prevent copying shall be taken (e.g. activation of Macrovision). However, this excludes the analogue video component interface, which is handled separately (see clause 7.4.3).

7.4.3 Component video control

Restrictions regarding the analogue component video interface (YPbPr) are signalled in ECMs defined by the CA system provider listed in clause 7.1.

7.4.4 Storage rights

This clause is only valid for PVR enabled IRDs which have an embedded CA System.

For IRDs where the CA System reside on an external CI Plus CA module please refer to 7.4.5.

7.4.4.1 Basic rules

In cases where the HDTV IRD has an internal or an external storage capability, the storage rights information shall be signalled in ECMs defined by the CA system provider listed in clause 7.1.

The HDTV IRD shall be able to handle and observe the following storage rights:

- No restrictions on storage of content
- Recording allowed but trick mode prohibited
- No recording allowed

These storage rights shall be stored together with the content and shall be observed during subsequent playback of the content ([31]).

7.4.4.2 Storage encryption

In case the HDTV IRD has an internal or an external storage capability, activation of storage encryption shall be signalled in ECMs defined by the CA system provider listed in clause 7.1.

The HDTV IRD shall provide an encryption system for local encryption of content which is stored on an internal or external storage device.

The HDTV IRD shall provide a decryption system for local decryption of content, which was previously stored encrypted on an internal or external storage device.

7.4.4.3 Playback Trick mode control

In case the HDTV IRD has an internal or an external storage capability, the restrictions on playback trick modes shall be signalled in ECMs defined by the CA system provider listed in clause 7.1.

7.4.5 Storage Rights for IRDs with non-embedded CA System

In case the CA System resides on an attached CA Module, scrambled services shall be processed and recorded according to the Usage Rule Information signaled by the CA Module (see [23]).

The temporary stored content shall be scrambled and should be removed after expiry.

Non scrambled Services shall be recorder in clear and without any access restriction at all.

7.5 General rules on content immutability

The subsequent clauses are required for service providers having additional needs in securing the immutability of their programme signals.

The HDTV IRD shall provide technical means to observe these requirements.

7.5.1 No modification to programme signals

The HDTV IRD shall not allow the modification of the original programme signal by any service provider other than the original one. This is not limited to but includes, for example, insertion or replacement of advertisements.

7.5.2 No graphical overlays

The HDTV IRD shall not allow any graphical overlays on top of the original programme signal by any service provider other than the original one, regardless of whether the overlays appear on the whole screen or on parts of the screen.

The display of general (neutral) information such as information on the present/following programme and IRD related information displayed as part of the navigator (e.g. menus) are allowed.

This section does not apply to Applications which are directly related to the tuned broadcast signal like HbbTV applications or Teletext which are transported or at least signaled inside the currently decoded and displayed DVB broadcast service.

7.5.3 No concurrent display of programme signals and other content

The HDTV IRD shall not allow the concurrent display of the programme signal and any other content (video, images, text), such as by a split screen mechanism, unless the original service provider issues explicit permission for this or in the case of picture in picture functionality.

The display of general (neutral) information such as information on the present/following programme and IRD related information displayed as part of the navigator (e.g. menus) are allowed.

This section does not apply to Applications which are directly related to the tuned broadcast signal like HbbTV applications or Teletext which are transported or at least signaled inside the currently decoded and displayed DVB broadcast service.

7.5.4 No rescaling of the programme signal

The HDTV IRD shall not allow the rescaling of the programme signal except in non-discriminatory EPGs and/or navigators, or as part of picture in picture functionality.

7.5.5 No automatic Ad Zapping

The HDTV IRD shall not allow automatic ad zapping, for example tuning to another service during advert breaks.

This also applies to the playback of recorded content (see clause 8.)

8 DIGITAL VIDEO RECORDER (DVR)

All clauses herein apply only to HDTV IRDs with internal or external storage capabilities (DVR).

8.1 Content security

The recorded content shall be accessible and decodable at any time. The access and decoding of the recorded content shall be in compliance with clause 7.4.

The DVR should display information about content security restrictions inside an EPG and in information concerning the present/following programme based on the EIT Schedule and EIT present/following based on the copy-control descriptor as described in clause 7.4.

All content security restrictions in force at the time of recording shall be observed during playback of the content.

8.2 DVR scheduling

If the recording time is scheduled via an EPG, the recording process of the DVR should be triggered via the information concerning the present/following programme (EIT present/following).

8.3 Maturity rating

The maturity rating information (see also clause 7.3) shall be stored together with the recorded content and shall be processed during subsequent playback of the content.

9 HYBRID BROADCAST TELEVISION

If the HDTV IRD is able to connect to internet services, the HDTV IRD shall be able to process Hybrid Broadcast Television Applications in compliance with ETSI TS 102 796 V1.1.1 [25]. This requirement is valid until 31th March 2015.

HDTV IRDs submitted for certification after 31th March 2015 shall be able to process Hybrid Broadcast Television Applications in compliance with ETSI TS 102 796 V1.2.1 [28].

10 SYSTEM SOFTWARE UPDATE

The HDTV IRD shall provide a software download mechanism for the download of software modules. The manufacturer is responsible for providing a secure download mechanism safe from failure.

The system software update mechanism shall comply with state-of-the-art and approved security mechanisms.

The HDTV IRD software download mechanism shall provide a facility for replacing the existing system software with another.

User preferences settings and channel lists shall be preserved. In cases where this cannot be guaranteed, the user shall be explicitly informed that user settings will be affected during the update process.

Update mechanisms required by the CA system vendor shall be supported. The actual download process should be initiated by the user.

The progress of the update procedure shall be displayed on screen.

The update procedure shall be designed in such a way that the user can interrupt the update procedure any time without corrupting the currently installed IRD system software.

Any security aspects regarding system software updates shall be in the responsibility of the HDTV IRD vendor.

The HDTV IRD vendor and/or its representative in the Austrian market shall be fully responsible for all software updates, and guarantees an update if necessary.

The HDTV IRD vendor and/or its representative in the Austrian market will indemnify ORS for all possible claims in regard to downloads to the HDTV IRD.

10.1 SSU over-the-air (broadcast download)

The HDTV IRD should be capable of establishing a system software update (SSU) via broadcast download. This may be done in accordance with [13].

In cases where the new system software is broadcast via ORS transponders, the HDTV IRD manufacturer shall provide:

- a TS-File for cyclic broadcast; and
- the necessary descriptors/parameters that are to be signalled.

10.2 Local download

It shall be possible to make downloads using a local data interface. The HDTV IRD manufacturer shall define the protocol mechanisms. The actual download is in the user's responsibility.